

**CHI MEI CORPORATION**

59-1 SAN CHIA, JEN TE, TAINAN HSIEN 717 TW

**PA-757(+)****Acrylonitrile Butadiene Styrene (ABS), "Polylac", furnished as pellets**

	<b>Min Thk</b>	<b>Flame</b>			<b>RTI</b>	<b>RTI</b>	<b>RTI</b>
<b>Color</b>	<b>(mm)</b>	<b>Class</b>	<b>HWI</b>	<b>HAI</b>	<b>Elec</b>	<b>Imp</b>	<b>Str</b>
<b>ALL</b>	<b>1.57</b>	<b>HB</b>	<b>4</b>	<b>0</b>	<b>85</b>	<b>80</b>	<b>85</b>
	<b>3.17</b>	<b>HB</b>	<b>3</b>	<b>0</b>	<b>85</b>	<b>80</b>	<b>85</b>

Comparative Tracking Index (CTI): **0**

Dimensional Stability (%): -

High-Voltage Arc Tracking Rate (HVTR): **1**High Volt, Low Current Arc Resis (D495): **1**

Dielectric Strength (kV/mm): -

Volume Resistivity (10xohm-cm): -

**(+) - Optional prefix or suffix may be used to denote 0-0.5% acid scavengers.**

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.

Report Date: 1983-06-23

Last Revised: 2007-09-20

Underwriters Laboratories Inc®

